

Variable Types Of Glass Tube Transmitter**MODEL NO : GT-555-FL-4-20****Glass tube transmitter**

"BOMBAY INSTRUMENT MFG. CO." make High accuracy, Fully enclosed , GLASS TUBE ROTAMETER having Flanged ends at Top & Bottom both of SS.304 material with output 4-20 mA having detail specification as follows.

Model No	:	GT- 555 – FL- 4-20
TYPE	:	Direct On-line
Metering Tube	:	Borosilicate German Taper glass tube
Casing	:	M.S. Casing from 2 sides & clear acrylic Front & back
Scale	:	Engraved on milky white acrylic
Gland packing	:	PTFE
Accuracy	:	+/- 2% Of F.R
Float	:	SS.316 , Conical
Inlet/outlet	:	Bottom to Top
Connection	:	Flanged 2" NB, ANSI 150 # RF
Service	:	Brine
Flow Rate	:	0.89 To 8.91m ³ /Hr
Out Put	:	4-20mA
Supply	:	24V DC
All wetted Parts	:	As Per Requirement
Make	:	BIMCO
Qty	:	Please Confirm

Certificate :- Calibration Certificate along with Copy of Master Calibration report Traceable to NABL Accredited Lab OR International USA Factory

Manufactured & Marketed By:**M/S. Bombay Instrument Mfg. Co.**

SHOP NO. 5, 50/86, JITEKAR WADI

OPP. VINAY HOTEL 88, THAKURDWAR ROAD MUMBAI – 400 002 - INDIA

Tel. : 91 (022) 2389 1073 / 2389 10 7 5

Fax : 91 (022) 2389 1075

Web. : www.bombayinstrument.in

Email : bimco@mtnl.net.in , bimcoindia@gmail.com